

OZAUKEE COUNTY

U.S. PUBLIC LAND SURVEY MONUMENT RECORD

Note: This form is intended and designed to fulfill all requirements of Wisconsin Administrative Code, Chapter A-E 5.02, U.S. Public Land Survey Monument Record (3)(a)(b)(c)(d)(e)(f)(g)(h)(i).

(a) CORNER LOCATION: SW SECTION 27

TOWNSHIP 12 NORTH

RANGE 22 EAST

BELGIUM
TOWN/CITY/VILLAGE _____

STATE PLANE COORDINATES OF CORNER: _____
NORTH _____
EAST _____

ELEVATION OF CORNER: _____ THETA ANGLE: _____

Horizontal Datum: Wisconsin State Plane Coordinate System, South Zone
NORTH AMERICAN DATUM 1927 1983

Vertical Datum: National Geodetic Vertical Datum of 1929

(b)(f)(g)(h) Description of monument found at this corner and if it was accepted, state all evidence (material, testimonial, occupational, plats, records, other monuments) used as a basis for accepting. If not accepted or if nothing was found, state evidence used as a basis for establishing location. If reestablished through lost corner proportionate methods, indicate all monuments, distances and directions used to establish.

Using six existing concrete witness monuments, found
pk nail in pavement surface. Railroad spike below pk nail.
Pieces of broken limestone found below railroad spike.
Accepted pk nail as corner and replaced with Berntsen
Aluminum monument with a three inch riser.

INDEX NO 137

